



Water Bowser *18-20m³*



TRUCK AHEAD OF THE COMPETITION

Fuel Economy | Powerful Engine | Excellent Load Carrier



SPECIFICATION | Water Bowser-18-20m³

BASIC INFORMATION	Drive Style	6*4
	Steering Wheel Position	Right Hand Drive
	Platform	EST
	Vehicle Model	BJ3259DLPKE-RA
CHASSIS DIMENSIONS PARAMETERS	Wheelbase (mm)	4100+1350
	Length (mm)	10000
	Width (mm)	2545
	Height (mm)	3500
COMPLETE VEHICLE MASS PARAMETER	Chassis kerb weight (kg)	10125
	GVW (kg)	55000
COMPLETE VEHICLE PERFORMANCE PARAMETER	Maximum speed (km/h)	70
	Max climbing capacity % (full load)	30
CAB	Body Type	EST-2490 - Flat Roof with A/C
	Carrying Number	2
ENGINE	Engine Model	ISGe3-350
	Displacement (L)	10.5
	Max power (ps/hp/rpm)	257/350/1900
	Max torque (Nm/rpm)	1800/1000
	Engine Brand	Cummins
	Emission	Euro III

CLUTCH	Clutch Type	430 Pull Type Diaphragm Spring Clutch
	Plate Diameter	430
GEARBOX	Gearbox Model	HW19712
	Gearbox Brand	DACHI 12MT
SUSPENSION	Front Suspension/ Leaf Spring Number	9
	Rear Suspension/ Leaf Spring Number	12
FRONT AXLE	Front Axle Rated Load	9T
	Front Axle Brake Type	Drum Brakes
REAR AXLE	Rated Load/ Gear Ratio	16T/BENZ 16T/5.73
	Rear Axle Brake Type	Drum Brakes
TYRE	Tyre Model	12.00R20 20PR
	Tyre Quantity	10+1
FRAME	External width (mm)	F865mm/R865mm
	Stringer cross section (mm)	225/320×90× (8+7)
STEERING GEAR	Steering Gear Model	AM105L-SR
FUEL TANK	Fuel Tank Capacity & Material	350L (Aluminum alloy)

2 years Warranty on Complete Unit / Unlimited Mileage

Gareth Evans - +263 772 125 764 | Siwela Hatityi - +263 772 214678